



BGAN terminals

A quick reference guide




Inmarsat's Broadband Global Area Network service – BGAN – is accessible via a small, lightweight, satellite terminal, which is quick to set up and easy to use. And you can use the same device worldwide.


A range of terminals is available, providing performance options to suit different operational needs. The service is accessed via BGAN LaunchPad, a software interface, which is standard across all terminals.


							
	Wideye™ Sabre™ I Voice and data, single-user device	EXPLORER® 110 Smallest, lightest device in the range	EXPLORER® 300 Highly compact, robust device	EXPLORER® 500 High bandwidth, highly portable device	HNS 9201 High performance, multi-user device	EXPLORER® 700 Multi-user device with extensive functionality	
Standard terminals	Manufacturer:	Addvalue Communications www.wideye.com.sg	Thrane & Thrane www.thrane.com	Thrane & Thrane www.thrane.com	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hns.com	Thrane & Thrane www.thrane.com
	Size:	259 x 195mm (1.6kgs)	200 x 150mm (<1kg)	217 x 168mm (1.4kgs)	217 x 217mm (<1.5kgs)	345 x 275mm (2.8kgs)	297 x 399mm (3.2kgs)
	Standard IP:	Up to 240/384kbps (send/receive)	Up to 240/384kbps (send/receive)	Up to 240/384kbps (send/receive)	Up to 448/464kbps (send/receive)	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)
	Streaming IP: (send & receive)	32, 64kbps	32, 64kbps	32, 64kbps	32, 64, 128kbps	32, 64, 128, 256kbps	32, 64, 128, 256kbps
	ISDN:	N/A	N/A	N/A	64kbps via USB	64kbps via RJ-45	64kbps via ISDN RJ-45
	Voice:	Via RJ-11 or Bluetooth handset/headset	Via RJ-45 ISDN or, Bluetooth handset	Via RJ-11 or Bluetooth handset/headset	Via RJ-11 or Bluetooth handset or 3.1kHz audio	Via RJ-45 ISDN handset, via ISDN TA w/two RJ-11 ports or 3.1 KHz audio fax	Via RJ-11 (x2), Bluetooth handset or 3.1kHz audio
	Data interfaces:	Ethernet, Bluetooth	Ethernet (with adapter), USB, Bluetooth	Ethernet, Bluetooth	Ethernet, USB, Bluetooth	Ethernet, USB, WLAN 802.11b	Ethernet (x2), USB, Bluetooth, WLAN 802.11g, Digital I/O
Ingress protection:	IP 54	IP 44	IP 54	IP 54	IP 55	IP 52 (terminal), IP 66 (antenna)	

Vehicular terminals

		
	EXPLORER® 527 Multi-user, tracking antenna	HNS 9250 Multi-user, tracking antenna
Manufacturer:	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hns.com
Size:	Terminal 403 x 483mm (5kgs) Antenna 500 x 150mm (5kgs)	Terminal 275 x 345mm (2.8kgs) Antenna 477 x 153mm (5.0kgs)
Standard IP:	Up to 448 / 464kbps (send / receive)	Up to 448 / 464kbps (send / receive)
Streaming IP: (send & receive)	32, 64, 128kbps	32, 64, 128kbps
ISDN:	N/A	N/A
Voice:	3.1kHz, 2-wire phone/fax	Via RJ-45 ISDN handset, via ISDN TA w/two RJ-11 ports or 3.1 KHz audio fax
Data interfaces:	Ethernet	Ethernet, ISDN, WLAN 802.11b
Ingress protection:	IP 56 antenna	IP 56 antenna

Encrypted terminal

	
	AN/PSC-14(c) Integral IP encryption (US only)
Manufacturer:	ViaSat, Inc. www.viasat.com
Size:	Terminal 287 x 420mm (9.3kg) Antenna 430 x 275 (2.6kg)
Standard IP:	Up to 258 / 422kbps (send / receive)
Streaming IP: (send & receive)	32, 64kbps
ISDN:	N/A
Voice:	Via 5/6 pin audio, RJ-11, ISDN handset
Data interfaces:	Ethernet (red and black), USB
Ingress protection:	IP 67



How to buy BGAN

BGAN is available through Inmarsat distribution partners and service providers in more than 80 countries. Visit our website to find the right partner for your organisation.

inmarsat.com/bgan

Whilst the above information has been prepared by Inmarsat in good faith, and all reasonable efforts have been made to ensure its accuracy, Inmarsat makes no warranty or representation as to the accuracy, completeness or fitness for purpose or use of the information. Inmarsat shall not be liable for any loss or damage of any kind, including indirect or consequential loss, arising from use of the information and all warranties and conditions, whether express or implied by statute, common law or otherwise, are hereby excluded to the extent permitted by English law. INMARSAT is a trademark of the International Mobile Satellite Organisation, Inmarsat LOGO is a trademark of Inmarsat (IP) Company Limited. Both trademarks are licensed to Inmarsat Global Limited. © Inmarsat Global Limited 2007. All rights reserved. BGAN terminals July 2007.